

A74 | CD1751260

Box IPC with Intel® Core™ Duo Prozessor



- Designed for 24 hours continuous operation
- Fanless, passive cooled
- Especially compact design and low consumption device
- By request without any rotating part
- Analogous RGB and optional DVI output make an easy activation of all 4:3, 16:9 and 16:10 formats
- The IPC can be booted through the network and from external USB-devices
- Works as a standalone appliance or can be integrated into all Reikotech big screens
- Made in Germany

Technical Specifications

Embedded Board	Mini ITX Format
CPU / Intel® Core™ Duo	2 GHz (T2500)
SDRAM DDR	4 GB
Chipset	Intel® 945 GM and ICH7M
VGA	Intel® extrem GMA 950 (Graphic Media Accelerator) up to 224 MB shared Memory 2048 x 1536 at 75 Hz
Expansion possibility	1x PCI Slot
Interfaces	4 USB Ports 2.0 2x LAN RJ45 10 / 100 MBit, 1 GigaBit 2 serial keyboard, mouse VGA
Switches front mounted	1x Power Switch 1x Power ON / OFF 1x Reset
Memory StorageCapacity(min)	2,5" HDD(60GB), SSD (8GB) or CF (4GB)
Power Supply	115 / 230 VAC
Power Consumption	27 W (idle mode) 35 W (50% CPU load) 44 W (100% CPU load)
Operating temperature	0°C up to 50°C
Dimensions	Height 90 mm Widht 310 mm Depth 230 mm
Options	Completely without rotating parts Audio output (7.1 Surround) Integration into Reikotech big screens Optional equipment All available RAL colours

Reikotech Systems GmbH - Hermann-Bössow-Str. 20 - 23843 Bad Oldesloe
Tel.: 04531 1784-29 Fax: 04531 8 12 88 www.reikotech.com e-mail: sales@reikotech.com