

A8015TFT001

15,0” Infomedia Panel PC



- **Integrated PC**
- **Also as on-board TFT-Multimediasystem for roadway arrangement and other information available**
- **Shapely, compact and solid aluminum construction with a very “slim” installation depth of only 55 mm and dustproof assembling**
- **Anti-reflective coating on both sides**
- **Made in Germany**

Technical Specifications

Resolution	1024 x 768
Vertical frequency	50 Hz - 85 Hz
TFT	15,0" active matrix flat screen typ. 400 cd/m ² Contrast 400:1 16,7 Mio. Colours
Control elements / Switches	VESA 75 x 75 assembly
Supply voltage	24 VDC nominal
PC-Unit	IPC Intel Celeron M, fanless, passive cooled 1 GHz 512 MB DDR-SDRAM min. 2GB Memorycard
Operating temperature	-20°C to 60°C (operating temperature) (surrounding, restricted , temporary) -30°C to 85°C (storage temperature)
Humidity	0-90% max. (non condensing)
Weight	ca. 26 kg (Ausstattungsabhängig)
Colour	RAL 7035
Dimensions H x W x D	366mm x 290mm x 72mm
Manufactured in compliance with	EINEN50155, 50121-2-3, 61373 CE-Zeichen
Optionen	Custom colours mounting kit IBIS Interface Infomedia Software

Reikotech Systems GmbH - Hermann-Bössow-Str. 20 - 23843 Bad Oldesloe
Tel.: 04531 1784-29 Fax: 04531 8 12 88 www.reikotech.com e-mail: sales@reikotech.com

Specifications are subject to minimal changes due to production and improvement of the product!
Rev.: 10/2009