



A8017TFT002

17" Infomedia Panel PC



- **Integrated PC**
- **Also as on-board TFT-Multimediasystem for roadway arrangement and other information available**
- **Shapely, compact and solid aluminum construction with a very “slim” installation depth of only 85 mm and dustproof assembling**
- **Anti-reflective coating on both sides**
- **Made in Germany**

Technical Specifications

Resolution	1280 x 1024
Vertical frequency	50 Hz - 75 Hz
TFT	17" active matrix flat screen typ. 400 cd/m ² Contrast 1000:1 16,7 million colours 85° / 85° hor. 80° / 80° vert.
Control elements / Switches	RJ45 Ethernet USB 2.0 Power supply
Supply voltage	115 / 230 VAC, 50 / 60 Hz
PC-Unit	IPC Intel Celeron M, passive cooled 1 GHz 512 MB DDR-SDRAM mind. 2GB Memorycard
Operating temperature	-20°C to 60°C (operating temperature) (surrounding, restricted , temporary) -30°C to 85°C (storage temperature)
Humidity	0-90% max. (non condensing)
Weight	5.5 kg
Dimensions	ca. 400 x 333 x 85 [mm]
Manufactured in compliance with	CE Zeichen
Options	Custom colours Mounting kit 24 VDC Power supply Suitability for trainapplications according to EN50155 IBIS interface Touchscreen

Reikotech Systems GmbH - Hermann-Bössow-Str. 20 - 23843 Bad Oldesloe
Tel.: 04531 1784-29 Fax: 04531 8 12 88 www.reikotech.com e-mail: sales@reikotech.com